



# EPR250

## Cost- Effective Receipt Printer

*Unbeatable Value, Unmatched Performance*

- Multiple Interfaces Options, Multiple Language Supported.
- 4M Large Cache, Supporting 58/80mm Switching,
- Automatic Overheating Protection Function For Printhead
- Visualized Paper Bin With Multiple Color Flip Option.
- Paper Saving Function.
- AOI Printhead & Rohm Printhead from Japan
- High Quality and Durable.



# EPR250

## Receipt Printer



Printing	
<b>EPR250</b>	
Printing method	Direct thermal
Column capacity	576 dots/line or 512 dots/line
Printing speed	230mm/s
Interface	USB+Lan
Printing paper	80mm
Line spacing	3.75mm(Adjustable by commands)
Print command	ESC/POS
Column number	80mm paper: Font A - 42 columns or 48 columns/ Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots Simplified/Traditional Chinese: 24x24 dots
Graphics	Monochrome BMP and other image files can be downloaded to FLASH
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC437(Standard Europe)/Katakana/PC850(Multilingual)/PC860(Portuguese)/ PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/ Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)
1D code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
2D code	QR CODE / PDF417
Buffer	
Input buffer	256Kbytes(Lan, USB+Lan)
Power	
Power adaptor	AC 100-240V/50~60Hz
Power source	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Physical characteristics	
Weight	0.92 KG
Dimensions	180*140*127mm
Environmental Requirements	
Work environment	Temperature (0~45 ) humidity(10~80%)(non-condensing)
Storage environment	Temperature(-10~60 ) humidity(10~90%)
Reliability	
Cutter life	1.5 million cuts
Printer head life	150KM
Driver	Windows / Linux

